

AN1165 - LFPAK56/PowerDI5060 Compatible Footprint

Muhammad Zafar Kausar, Automotive BU, Diodes Incorporated

This document compares the LFPAK56 package to Diodes Incorporated's PowerDI5060 package and provides a new footprint which can accommodate both devices while minimizing the copper area.

Note: Figures included in this document are not to scale. All dimensions given are in mm.

PowerDI5060 Footprint





Figure 1: Diodes' PowerDI5060 footprint Table 1: PowerDI5060 footprint dimensions

Diodes' PowerDI5060 footprint can be seen above. It shows four pins on top which are all connected to the central drain tab. Three of the four pins at the bottom are connected to the source while the remaining pin is connected to the gate. The package outline has been shown in grey while the pads (copper area) are shown in red.



LFPAK56 Footprint

The LFPAK56 is similar, although instead of four exposed pins connecting to the drain, there is only one large pad, as shown below:



Figures 1 and 2 show both footprints with their dimensions. The dimensions of both packages and their footprints are similar. To visualize and compare these better, Figure 3 below shows an overlapping image of both footprints.




Figure 3: PowerDI5060 footprint overlapped with the LFPAK56 footprint

AN1165 - Rev 3 2 of 5 September 2021 © Diodes Incorporated Application Note



Compatible footprint

A compatible footprint was created by combining the two footprints above and making minor adjustments. The four drain pins in the PowerDI5060 were replaced with one large pad, as in the LFPAK56. The width of the central tab on the PowerDI5060 was increased to match the width of the LFPAK56. The widths and heights of the source and gate pins were also adjusted to accommodate both packages. The resulting footprint is shown below:




Figure 4: LFPAK56/PowerDI5060 compatible footprint Table 3: Compatible footprint dimensions




Figure 5: PowerDI5060 (left) and LFPAK56 (right) on new compatible footprint



As shown in Figure 5, both footprints are compatible with the new footprint. In Figures 6 and 7 below, both packages can be seen on the new footprint in the 3D view.




Figure 6: PowerDI5060 (left) and LFPAK56 (right) on new compatible footprint (top view)




Figure 7: PowerDI5060 (left) and LFPAK56 (right) on new compatible footprint (bottom view)



IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel

Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

- A. Life support devices or systems are devices or systems which:
 - 1. are intended to implant into the body, or
 - 2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.
- B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the

failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2018, Diodes Incorporated

www.diodes.com